

**Clarke®**

***Encore 20 Series*** Compact Scrubber



# Compact Automatic Floor Scrubbers for Heavy Duty Cleaning Applications

## Designed To Last ...

Encore compact autoscrubbers can be found cleaning hospitals, schools and even a variety of heavy industrial applications. This versatile unit is rugged and dependable, even in the harshest of conditions. After many years of use the Encore standard and luxury models still provide the greatest value in the industry.

## Encore Features Include:

- Heavy-duty Polydur® construction protects internal components.
- Reinforced floating scrub deck.
- Transaxle drive is standard on the luxury model for scrubbing inclines and ramps and offers a tremendous advantage when transporting the machine.
- Patented Accu-Track™ break-away squeegee prevents damage if accidentally hooked by a post or pallet. The connecting hose stays with the machine.
- Heavy duty rear caster absorb shocks from grouted or damaged floor surfaces.
- Optional brushes will increase cleaning effectiveness on rough concrete covered with grease and grime.
- Optional off-aisle spray tool and vac wand.
- Various battery pack options mean you only pay for the run time you need.



# Service is a Breeze with Encore Automatic Scrubbers



Operator controls feature electronic, infinitely variable, solution control that eliminates cables and linkages. Brush lift and squeegee lift handles are within easy reach. Circuit breakers, charger plug, and drain hoses are conveniently located.




Patented squeegee and footprint design provides perfectly dried floors even in the tightest of turns.

# ENCORE™ 20 Series

## Compact Automatic Walk-Behind Scrubbers

# Clarke®

Division of  
**ALTO®**



### KEY FEATURES

- Operator comfort
- Stylish design
- Extended run times
- Large capacities for a compact scrubber
- Impressive warranties

## SPECIFICATIONS

Model	Encore S20E	Encore S20 / Encore L20
Power Supply	115V, 60 Hz / 230V, 50 Hz	24V (2-12V), 95 AH or 195 AH
Charger	n/a	115V 60 Hz or 230V 50 Hz
Vacuum Motor	2-stage tangential discharge / 1 HP (.75 kW)	3-stage tangential discharge / .75 HP (.56 kW)
Brush Motor		Permanent magnet / .75 HP (.56 kW)
Traction Motor	Brush assisted	Permanent magnet / .75 HP (.56 kW)
Cleaning Swath		20 in. (50.8 cm)
Brush Down Pressure	Floating	Floating Pressure = 55 lbs. (25 kg) / Locked Down = 105 lbs. (48 kg.)
Brush Size / Speed		20 in. / 200 rpm
Traverse Speed	Brush assisted	Forward brush assisted / reverse not applicable for S20
Forward / Reverse		Variable forward to 250 ft. (76 M) /min. and reverse to 190 ft. (58 M) / min. for L20
Recovery / Solution Tank		14 / 14 gal. (53.2 / 53.2 L)
Squeegee Size / Type		27 in. (69 cm) / Accu-Trac™ w/break-away feature
Drive Wheels / Caster	(2) 8 in. x 2 in. (20.3 cm x 5.1 cm) neoprene and (1) 4 in. x 1 in. (10.1 cm x 2.5 cm) swivel rear caster	
Dimensions L x W x H		52.5 x 22.25 x 43.5 in. (133.4 x 56.5 x 110.5 cm)
Machine Weight	242 lbs. (109.8 kg)	468 lbs. (212.3 kg) w/batteries
Shipping Weight	414 lbs. (187.8 kg)	607 lbs. (275.3 kg) w/batteries

### WHO USES THIS MACHINE?

- Cleaning contractors, in-house cleaning crews
- Schools
- Hospitals
- Government buildings
- Retail facilities

### WHAT DOES IT DO BEST?

- Ideal for scrubbing in confined areas
- Reduces costs of hard floor cleaning

### WHAT MAKES IT EASY TO USE?

- Ergonomically designed operator controls
- Highly maneuverable with excellent line-of-sight

### WHAT ENHANCES ITS PRODUCTIVITY?

- Large solution and recovery tanks
- Adjustable brush pressure

### WHAT ADDS TO ITS DURABILITY?

- Polydur® means strength (all poly parts)
- Long vacuum life
- Unmatched warranty

### WHAT ARE THE SAFETY FEATURES?

- Recovery float shut-off prevents recovery tank overflow
- Key switch prevents unauthorized use

### WHAT ARE THE OPTIONAL FEATURES?

- Parking brake
- Off-aisle wand, hoses and floor tools
- Maintenance-free 105 AH batteries
- ESP (recycling feature)
- Various brushes and floor pads

**Clarke®**

2100 Hwy. 265  
Springdale, AR 72764  
www.clarkeus.com

DISTRIBUTED BY:

Customer Service: 1-800-253-0367  
Fax Orders to: 1-800-825-2753  
Technical Service: 1-800-356-7274

©2003 ALTO U.S. Inc., All Rights Reserved. Specifications subject to change without notice. P/N 70328A