



PBU

Propane Stripper

- Designed for fast high production stripping
- Safety first – safety last
- Super clean catalytic converter
- 80% safety fill tank
- Large non-slip tires
- Centrifugal clutch
- E.P.A. Approved
- C.A.R.B. Approved

Available in 21 inch single brush

- Powered by the dependable, clean running 603cc Kawasaki twin V engine
- Rugged cast aluminum alloy housings
- Solution containment splash guards
- Impregnated supergrit brushes
- Battery start
- Hour meter aids in scheduling service intervals
- Powder coated finish resists oxidation and chemical damage – cleans easily and assists in maintaining appearance
- Built to tackle even the toughest floor stripping applications

Trusted. Reliable. Efficient.

A Nilfisk-Advance Brand

Clarke[®]



SPECIFICATIONS		PBU Propane Stripper 21 in
Part Number	56381410	
Model	21KBCATCLST	
Pad Size	21 in (53 cm)	
Engine	603cc Kawasaki V-Twin	
Dust Control	No	
Catalytic Muffler	Yes	
CARB Gard™	Yes	
Clutch	Yes	
Pad Speed	1,400	
Propane Tank	20 lb (9.1 kg) Capacity 80% Safety Fill	
Auto Fuel Shutoff	Yes	
Low Oil Shutoff	Yes	
Hour Meter	Yes	
Centrifugal Clutch	Yes	
Sound Level	87 dB A	
Productivity Rate	25,000 ft ² /hr (2,322 m ² /hr)	
Agency Approvals	EPA, CARB, and UL Listed	
C.A.R.B. Certified (California Air Resources Board)	Yes	
Weight (with empty tank)	242 lb	
Dimensions	Length 51.5 in (131.8 cm), Width 23.3 (59 cm), Height 43 in (109.2 cm)	
Warranty	2 Years Parts and Labor, 12 V battery warranted by manufacturer	

Specifications are subject to change without notice.

Ease of Use

- Battery start eliminates difficult manual pull start
- Ergonomically designed loop handle reduces operator fatigue
- Handle easily adjusts to operator height
- Tank changes made easy with drop-in holder and quick-snap fastener
- Large non-slip tires ease transport and control

Productivity

- Powerful 603cc engine maintains speed under heaviest loads
- Grit brushes strip old finish quicker
- Wide 21 inch scrub path

- Large 20 pound propane tank provides more working time between refills
- Automatic compression release reduces starter wear
- 1,400 RPM brush speeds strip faster
- Splash guards keep stripper solution under machine and assists with first pass performance
- Large non-slip tires assist with control of machine in slippery operations so operator can move faster

Safety

- Super clean catalytic converter aids with improved air quality

- Centrifugal clutch - brushes do not turn until engine rpm's are at working speed
- 80% fill tank reduces damage to propane system components from overfilling
- Low oil shut-down system protects engine
- Electrical fuel lock-off system stops gas flow when engine stops
- Total electrical shut-off system prevents battery drain when engine stops
- UL approved propane system components
- Non-slip tires give operator more control under slippery stripping conditions



©2011 Nilfisk-Advance, Inc. All rights reserved. P/N 79975A 6/11

14600 21st Avenue North • Plymouth, MN 55447-3408
Phone: 800.253.0367 • Fax: 800.825.2753

240 Superior Boulevard • Mississauga, Ontario, Canada L5T 2L2
Phone: 800.668.8400 • Fax: 800.263.5111

Clarke®