

Clarke®

BOS-18 Orbital Floor Machine



www.clarkeus.com

Clarke®

Cleaning Power Since 1916.

BOS-18 Orbital Floor Machine

Clarke®



Key Features

- 3600 1/4" orbits per minute
- Use for scrubbing, chemical-free stripping, and wood floor refinishing
- 4 gallon solution tank feeds cleaning solution to the pad
- Heavy cast components provide durability and aggressive scrubbing action
- Large non-marking transport wheels
- Powerful, totally enclosed motor requires less maintenance
- Ground Fault Circuit Interrupter (GFCI) eliminates the risk of electrical shock



PRODUCT

- Seamless chrome-plated handle tube resists rust, and increases durability.
- Totally enclosed fan cooled dual capacitor motor eliminates overheating
- Heavy cast iron main frame supplies weight for aggressive performance
- Cast aluminum pad driver plate reduces chance of bending

EASE OF USE

- No side torque
- Operates in any direction
- Dual switch levers for easy operation with either hand
- Convenient lifting handle
- Precision balanced counter weight and oversized drive bearing supply consistent performance, while reducing vibration

PRODUCTIVITY

- Large non-marking transport wheels protect finished areas from damage
- Full "harpoon" face pad driver effectively transfers motion to pad
- High weight and high speed orbital agitation provide aggressive cleaning

SAFETY

- Hospital grade plug assures electrical safety when connected to a properly grounded outlet
- Ergonomic dihedral handle with safety interlock offers operator comfort and protection
- Ground fault circuit interrupter (GFCI) eliminates possibility of electrical shock

SPECIFICATIONS

| | BOS-18 |
|------------------------|--|
| Part Number | 01555A |
| Cleaning Pad Size | 12" x 18" (30.5 x 45.8 cm) |
| Solution Tank Capacity | 4 gallons (15.1 L) |
| Motor | 1 HP (.75 kW) |
| Voltage / Frequency | 120 V / 60 Hz |
| Orbit Speed | 3600 orbits per minute |
| Orbit Diameter | 1/4" (6.4 mm) |
| Power Cable | 14-3, 50' safety yellow with GFCI |
| Sound Level | 75 dB(A) |
| Dimensions (L x W x H) | 18.6" x 20" x 45" (46.9 x 50.8 x 114.3 cm) |
| Weight | 112 lbs. (50.8 kg) |
| Warranty | 1 Year Parts & Labor |



Solution is applied to the pad when released by a manual trigger on the 4 gallon solution tank.



Power is supplied to the machine from any 120 volt, 15 amp outlet through a GFCI power cable that prevents electrical hazards.

Clarke®

2100 Hwy. 265
Springdale, AR 72764
www.clarkeus.com

DISTRIBUTED BY:

Customer Service: 1.800.253.0367
Fax Orders to: 1.800.825.2753
Technical Service: 1.800.356.7274

©2008 ALTO U.S. Inc., All Rights Reserved. Specifications subject to change without notice. P/N 70511A 10/08

