



## MC1200™ Dual-Surface Cleaner

### **Professional Dual Surface Cleaning**

The MC1200™ features an improved dual-surface design that significantly increases your cleaning capability. Using high pressure water at 1,200 psi for hard surface cleaning of tile and grout and other hard surfaces, the MC1200 easily loosens soils and immediately vacuums them up with a powerful 3-stage vacuum. This cleaning method leaves floors dryer than traditional methods and minimizes downtime. Auto-fill, auto-dump, and power priming significantly increase your productivity on the job by eliminating the need to stop work to fill or empty solution tanks. Then for professional carpet cleaning, switch to instant 212° F hot water with adjustable 150-500 psi.



- **Dual Surface Capable** for increased versatility, with a pump for 1,200 psi hard surface cleaning and a separate pump for instant 212° F hot water carpet extraction and adjustable pressure of 150 to 500 psi
- **Smart Circuit Locator** automatically locates separate lines to eliminate blown circuits
- **Patent Pending Hose Reel** – Built-in 25 foot vacuum and solution hose reel for easy hose management
- **Large 16 gallon Tank Capacity** provides longer run times
- **CRI Certified** – Third party tested and received the top GOLD certification for superior cleaning performance
- **Less Water Use (Combined with Higher Heat)** means faster drying, less chance of shrinkage, and less wicking from the pad
- **Heater Element** – In-line, after the pump, for longer life and instant heat up to 212° F
- **Low Moisture System** – Less water combined with higher heat means faster drying, less chance of shrinkage and less wicking from the pad
- **Tanks and Body** – Lightweight, rotationally molded with lifetime warranty against cracks, leaks, and dents
- **Cord Wrap** – Accommodates up to 50 feet of 12/3 electrical cord
- **Power Prime System** – Foot operated valve for easy priming
- **Top Warranty** – Industry leading, 2 year parts and labor warranty standard

**Trusted. Reliable. Efficient.**

# Clarke®

Specifications	MC1200™
Model Number	56384968 (complete package)
Vacuum	7.2 in, 3-stage vacuum
Shutoff	Ball & float
Pump	Positive displacement 1,200 psi pump, with adjustable pressure from 150-500 psi
Solution Pump	1,200 psi / 2.2 gpm
Waterlift	140 in
Heat	Instant to 212° F
Heater	2,000 Watt in-line heater
Wand	Evolution rotationally molded wand, twin tip for 500 psi, HFT-40 turbo hard surface tool
Weight	203 lb
Dimensions	H = 39 in x W = 21 in x L = 36 in
CRI Certified	GOLD

Specifications are subject to change without notice.



## Standard Features

- Patent pending, built-in hose reel
- Smart circuit locator
- Low moisture design
- 16 gallon solution tank
- 14 gallon recovery tank
- Chemical tray
- Two handles for easy maneuverability and loading
- Wand caddy for easy transport
- Dump hose, 22 inch height
- Auto-fill
- Power prime system
- Stainless steel pre-filter
- Auto pump, 5.5 gpm with electronic shut-off
- 10 inch non-marking wheels
- Low solution filling area for easy filling
- 25 foot high pressure solution line and crushproof vacuum hose
- Two detachable cords, 12/3 gauge, hospital grade plugs



# Clarke®

9435 Winnetka Avenue North  
 Brooklyn Park, MN 55445  
 Phone: 800.253.0367  
 Fax: 800.825.2753  
[www.clarkeus.com](http://www.clarkeus.com)

240 Superior Boulevard  
 Mississauga, Ontario, Canada L5T 2L2  
 Phone: 800.668.8400  
 Fax: 800.263.5111  
[www.nilfisk-advance.ca](http://www.nilfisk-advance.ca)