

# OZ40K™

## Ozone Generator



### Let the OZ40K™ clear the air for you

Ozone is the strongest oxidant commercially available and is a proven deodorizer. The OZ40K™ doesn't just cover up foul odors; it actually destroys the molecules that cause them. The OZ40K features a hermetically sealed severe application transformer that is designed specifically for harsh electrical and environmental demands imposed by continuous-duty corona discharge ozone generation. This transformer is a recognized UL component. The OZ40K has a high-density ceramic and stainless steel electrode corona discharge system, manufactured with stainless steel probes encased in ceramic with an outer stainless steel sleeve. There is no place for dirt or impurities to accumulate. They are maintenance free and are guaranteed for life, with no old fashioned plates to clean or corrode.



- **Versatility** – Excellent for fire restoration, eliminates tobacco and other smoke odors, removes mold, mildew, and other organic odors. Quickly deodorizes hotel/motel, hospital, and meeting rooms and excellent for freshening-up cars, buses, boats, and aircraft
- **Severe Applications Transformer** will provide increased operational performance and a longer service life
- **Tested and Proven** to maintain proper activated oxygen levels
- **Maintenance Free Corona Discharge System** provides proven constant ozone production and long service life
- **High Ozone Output Per Hour** increases performance and decreases time and labor
- **Consistent performance with No Downtime** for cleaning or reduced efficiency due to dirt or moisture build-up
- **Large Coverage Area** – Effective for areas up to 40,000 cubic feet
- **No Old Fashioned Plates or UV Tubes** to clean or break
- **Lightweight and Compact** for easy transport
- **Lifetime Warranty on Electrodes and Body**, three year limited warranty on transformer
- **Hermetically Sealed Patented Severe Application Transformer** – UL recognized component
- **Designed to Support Twice the Zone Generation Load** of a conventional transformer
- **Will Withstand Continuous Operation** in the most demanding of electrical and temperature environments



SPECIFICATIONS	OZ40K™
Part Number	56384970
Timer	30 hour programmable timer with adjustable ozone output levels
Transformer	Hermetically sealed patented severe application transformer – UL recognized component
Weight	13 lb
Dimensions	H = 8 in x W = 7 in x L = 22 in

Specifications are subject to change without notice.



**Note:** Ozone can be hazardous to organics such as plants, pets, and people. These type of organic items should not be present in a room when using the OZ40K™.



SNAP IT!



### Standard Features:

- High-density ceramic and stainless steel electrodes corona system
- 2.65 grams/hr, 2,650 mg/hr
- 30 hour programmable timer with adjustable ozone output levels
- Power supply overload protection
- Rotationally molded body with lifetime warranty
- 8 foot 16/3 gauge cord



Optional Car Kit

9435 Winnetka Avenue North • Brooklyn Park, MN 55445  
Phone: 800.253.0367 • Fax: 800.825.2753

240 Superior Boulevard • Mississauga, Ontario, Canada L5T 2L2  
Phone: 800.668.8400 • Fax: 800.263.5111

